

Table 1. Bear Deposit Drill Hole Intercepts

Company	Year	Drill Hole	Northing (UTM NAD 27)	Easting (UTM NAD 27)	Elevation (ft)	Inclination	Azimuth	Total Depth (ft)	From feet	To feet	Interval feet	% TCu	Interval X %TCu (GXT)
Anaconda	1961	B-01	310817.1	4320219.4	4360.1	-90°	-	2533	896	2,139	1,243	0.19	236
Anaconda	1962	B-02	310829.3	4320527.1	4357.3	-90°	-	2509.6	1,209	2,510	1,301	0.38	494
Anaconda	1962	B-03	310824.9	4320393.4	4358.4	-90°	-	864	Too Shallow				
Anaconda	1962	B-04	310641.8	4320201.1	4355.2	-90°	-	557	Too Shallow				
Anaconda	1963	B-05	310659.8	4320533.1	4357.3	-90°	-	1784.9	1,050	1,235	185	0.32	59
Anaconda	1963	B-06A	310835.9	4320682.5	4357.9	-90°	-	3516.2	1,590	3,288	1,698	0.39	662
Anaconda	1963	B-07	309923.9	4320588.8	4359.9	-90°	-	1982	Outside Mineralized Footprint				
Anaconda	1963	B-08	310546.5	4320932.6	4363.9	-90°	-	3607.1	1,377	2,650	1,273	0.29	369
Anaconda	1963	B-09	309929.9	4320953.4	4353.0	-90°	-	2149	Too Shallow				
Anaconda	1963	B-010	310836.7	4320925.2	4358.3	-90°	-	3709.3	1,736	3,392	1,656	0.38	629
Anaconda	1963	B-011	309949.8	4321404.2	4346.0	-90°	-	2148	Outside Mineralized Footprint/Too Shallow?				
Anaconda	1963	B-012	309957.1	4321708.9	4347.4	-90°	-	1458	Outside Mineralized Footprint/Too Shallow?				
Anaconda	1963	B-013	310840.3	4321077.6	4358.0	-90°	-	3680.4	1,929	3,436	1,507	0.42	633
Anaconda	1964	B-014	310850.4	4321229.8	4362.7	-90°	-	3650.4	1,355	3,370	2,015	0.32	645
Anaconda	1964	B-015	310065.6	4322067.0	4343.2	-90°	-	3166	2,163	2,458	295	0.28	83
Anaconda	1965	B-016	309980.1	4322669.5	4339.9	-90°	-	2096.7	Outside Mineralized Footprint				
Anaconda	1964	B-017	310988.8	4320921.5	4358.9	-90°	-	3703.4	1,319	3,703	2,384	0.38	906
Anaconda	1965	B-018	310634.5	4319894.3	4382.9	-90°	-	2015.9	Outside Mineralized Footprint				
Anaconda	1965	B-019	311442.8	4320678.7	4400.0	-90°	-	3329.3	2,510	3,329	819	0.26	213
Anaconda	1965	B-20A	312209.9	4320167.1	4366.5	-90°	-	2506.6	1,429	2,256	827	0.31	256
Anaconda	1966	B-021	311794.0	4320109.1	4412.0	-90°	-	4019	1,133	3,976	2,843	0.21	597
Anaconda	1966	B-022	311447.9	4321210.8	4422.2	-90°	-	4418.6	1,632	4,012	2,380	0.43	1,023
Anaconda	1966	B-023B	312241.2	4320768.7	4365.0	-90°	-	3059.1	1,597	2,649	1,052	0.50	526
Anaconda	1967	B-024	311445.2	4319640.1	4413.2	-90°	-	4793	2,781	4,211	1,430	0.30	429
Anaconda	1967	B-025	311443.7	4321054.5	4449.0	-90°	-	4340	1,815	3,323	1,508	0.30	452
Anaconda	1967	B-027	312830.1	4320876.1	4364.0	-90°	-	3833.8	Outside Mineralized Footprint				
Anaconda	1967	B-028	312679.0	4319370.6	4371.0	-90°	-	2840	Outside Mineralized Footprint				
Anaconda	1967	B-029	311558.2	4318945.3	4373.0	-90°	-	2743.5	937	1,514	577	0.27	156
Anaconda	1967	B-030	311878.5	4320958.8	4370.0	-90°	-	3177.5	No Significant Intercept				
Anaconda	1967	B-031	312395.0	4320864.9	4365.0	-90°	-	3008	2,474	2,964	490	0.55	270

Anaconda	1967	B-032	312277.3	4320469.6	4366.0	-90°	-	2403	1,169	2,403	1,234	0.28	346
Anaconda	1961	MH-1	311533.7	4320162.2	4524.1	-90°	-	1167.1	Too Shallow				
Anaconda	1961	MH 2	311403.8	4320418.8	4454.4	-90°	-	2374	1,802	2,374	572	0.17	97
Anaconda	1961	MH-3	311707.5	4320438.1	4510.0	-90°	-	102	Too Shallow				
Phelps Dodge	1969	L-01	312560.6	4320386.7	4378.1	-90°	-	3742.2	2,800	3,470	670	0.40	268
Phelps Dodge	1969	L-02	312243.7	4319807.5	4380.6	-90°	-	2297	1,360	1,900	540	0.42	227
Phelps Dodge	1970	L-03	311997.8	4319561.7	4381.8	-90°	-	3243.5	1,277	1,893	616	0.18	111
Phelps Dodge	1970	L-04	312495.0	4319796.6	4379.0	-90°	-	2980	Outside Mineralized Footprint				
Phelps Dodge	1970	L-05	312997.7	4320266.5	4375.0	-90°	-	3900	2,900	3,900	1,000	0.40	400
Phelps Dodge	1970	L-06	312511.1	4320660.0	4377.3	-90°	-	2983	No Significant Intercept				
Phelps Dodge	1970	L-07	312500.5	4320173.6	4378.6	-90°	-	3249	Outside Mineralized Footprint				
Phelps Dodge	1970	L-08	313478.6	4320244.7	4373.4	-90°	-	3004	1,660	2,290	630	0.40	252
Phelps Dodge	1973	L-12	311336.6	4318753.0	4394.7	-90°	-	2305	820	1,320	500	0.31	155
SPS	2016	GHH-001	310543.2	4319490.5	2017.5	-90°	-	2017.5	Outside Mineralized Footprint				
SPS	2015	B-048	312243.5	4320761.2	4368.3	-90°	-	3438	1,573	2,731	1,158	0.42	486
SPS	2015	B-049	311446.2	4321445.9	4358.4	-90°	-	3635	1,588	2,926	1,338	0.22	294
SPS	2015	B-050	312341.5	4321073.8	4366.0	-90°	-	3838	2,429	2,951	522	0.36	188
SPS	2016	B-051	311798.2	4321411.0	4366.4	-90°	-	3878	2,191	3,675	1,484	0.26	386
SPS	2016	B-052	311881.7	4321613.0	4360.3	-90°	-	3468	2,081	2,748	667	0.14	93
SPS	2023	B-053A	310778.0	4321510.0	4351.0	-60°	210	3503	2,212	3,138	926	0.31	287
SPS	2023	B-054	310406.0	4321602.0	4364.0	-70°	205	3458	2,311	3359	1,048	0.26	272
SPS	2024	B-055	309644.0	4321234.0	4350.0	-60°	180	3435	Outside Mineralized Footprint				
SPS	2024	B-056A	311175.0	4321411.0	4350.0	-65°	190	3613	1,237	3,613	2,376	0.40	950